



火焰加热器 FLAME HEATER

管道火焰加热器广泛应用于钢管焊接前的预加热。
使用液化可燃气体，通过均匀分布的火焰加热喷嘴对管道进行预热。环形加热器上安装有六个对称的转轮安放在管道上转动使得加热均匀。加热器采用两个半圆合页对开安装方式，安装极为容易。

Flame heaters are widely applied on steel pipe preheating prior to welding.

To fuel with liquefied flammable gas, pipes are preheated by the flame from jet nozzles in uniform distribution around the ring. There are 6 symmetrical rollers on the flame heater, running along the preheated pipe, to ensure even heating effect. Its hinged split semicircle design is for easy installation

专利PATENT: ZL201220126865.9

技术参数 TECHNICAL SPECIFICATIONS >>>

规格型号 MODEL	JRQ-14	JRQ-16	JRQ-20	JRQ-24	JRQ-26	JRQ-28	JRQ-32	JRQ-36	JRQ-40	JRQ-48	JRQ-58	JRQ-66	JRQ-80
适用管径 APPLICABLE PIPE DIAMETER	Φ355	Φ406	Φ508	Φ610	Φ660	Φ711	Φ813	Φ914	Φ1016	Φ1219	Φ1473	Φ1676	Φ2032
喷嘴数量 NOZZLE NUMBER	6	6	8	8	10	10	10	12	12	16	18	20	24



洛阳德平机械设备有限公司
Luoyang Deping Mechanical Equipments Co.,Ltd.

电话(Tel):+86-379-64280768 +86-15038590497
网址(Web):<http://www.lydpjx.com> www.dppipemachine.com
邮箱(Email): lydpjx@163.com